

MPS 6500 Series Continuous Band Sealer

The MPS 6000 series of sealers offer you the highest quality and utmost reliability of any machine on the market at the most effective price. Key design features include; a unique Teflon band tensioner, tool-less access to the seal section, removable sealing sections, the ability to easily add options to the machine in the field, customizable stands, and much more.

The MPS 6500 models are conveyorized bag sealers capable of sealing bags of any weight. These sealers are capable of sealing bags up to 6 mil in thickness at production rates (3 mil maximum when gusseted). The stainless steel 6" wide x 6' long conveyor comes with a food grade belt and guide rails. This conveyor can be manually raised and lowered to match any size bag. A line of 12" wide conveyor sizes are available as an upgrade for heavy duty applications.

Designed for 24/7 operation, these sealers are suitable for all production environments.



TECHNICAL SPECIFICATIONS

Electrical: 120 volts, 10 amps.

Infeed Direction: Right to Left.

Motor: Variable Speed DC drive

Seal Throat Depth: 70 mm / 2.75°

Sealing Section:

125 mm / 5" of heating.

125 mm / 5" of cooling.

Variable Speed:

Up to 12.7 m / 500" per minute.

Sealing Width:

6 mm / 1/4" standard. Vertical or Horizontal

Sealer

Operation:


0-230 degrees Celsius.

Temperature Range:

0-445 degrees Fahrenheit.

Temperature Controller: Digital PID autotune controller.

Model	Configuration
MPS 6500	Conveyorized Sealer
MPS 6510	Conveyorized Sealer with Front End Trimmer
MPS 6520	Conveyorized Sealer with Emboss Coder
MPS 6530	Conveyorized Sealer with Dry Ink Printer
MPS 6550	Conveyorized Sealer with Front End Trimmer & Dry Ink Printer
MPS 6560	Conveyorized Sealer with Front End Trimmer & Emboss Coder





PLEXPACK Machinery Distributed By:

Birnbeg Machinery, Inc 847+673-5242

www.bagsealers.com